

Supporting Information

## **Role of Graphene on Hierarchical Flower-like NiAl Layered Double Hydroxide-Nickel foam-Graphene as Binder-free Electrode for High-rate Hybrid Supercapacitor**

Luojiang Zhang <sup>a</sup>, K.N. Hui <sup>b,\*</sup>, K.S. Hui <sup>a,\*\*</sup>, Xin Chen <sup>a</sup>, Rui Chen <sup>c</sup>, Haiwon Lee <sup>c</sup>

<sup>a</sup> Department of Mechanical Convergence Engineering, Hanyang University, 17 Haengdang-dong, Seongdong-gu, Seoul 133-791, Republic of Korea


<sup>b</sup> Institute of Applied Physics and Materials Engineering, University of Macau, Avenida da Universidade, Taipa, Macau

<sup>c</sup> Department of Chemistry, Hanyang University, 17 Haengdang-dong, Seongdong-gu, Seoul 133-791, Republic of Korea

\* Corresponding author. Fax: +853 8822-2426; Tel: +853 8822-4422; [bizhui@umac.mo](mailto:bizhui@umac.mo) (K.N. Hui)


\*\* Corresponding author. Fax: +82-2-2220-2299; Tel: +82-2-2220-0441; [kshui@hanyang.ac.kr](mailto:kshui@hanyang.ac.kr) (K.S. Hui)

**Supporting information Figure S1.**




**Fig. S1** XRD patterns of LDH-NF (a), GO (b) and LDH-NF/GNS (c)

**Supporting information Figure S2.**



**Fig. S2** SEM images of (a) GO and (b) NF

Supporting information Figure S3.



**Fig. S3** (a) CV curves of GNS at various scan rates. (b) Charge-discharge curves of GNS at different current densities. (c) Specific capacitance of GNS at different current densities.

**Table S1** Comparison of electrochemical performance of the reported NiAl-LDH/carbon materials-based electrodes ( $C_s$ : specific capacitance)

Material Samples	$C_s$ (F g <sup>-1</sup> )	Current density (A g <sup>-1</sup> )	Cycle stability	$C_s$ after cycling test (F g <sup>-1</sup> )	Reference electrode	Ref
rGO nanocup/NiAl-LDH	2172.7 1174	1 50	30 A g <sup>-1</sup> , 5000 cycles, 98.9%	~1500	SCE	1
NiAl-LDH/C	1064 758	2.5 12.5	25 A g <sup>-1</sup> , 500 cycles, 50.5%	246.3	SCE	2
GNS/NiAl-LDH	781.5	10 mA cm <sup>-2</sup>	10 mA cm <sup>-2</sup> , 200 cycles, 122.6%	693.7	SCE	3
NiAl-LDH/CNT/rGO	1869 713.4	0.0625 6.25	0.625 A g <sup>-1</sup> , 1000 cycles, 96.5%	1200	SCE	4
a-GNS/NiAl-LDH	1730.2 790	0.1 10	5 A g <sup>-1</sup> , 500 cycles, 99.2%	976.2	SCE	5
NiAl-LDH array/GNS	1329 851	3.57 17.86	15.3 A g <sup>-1</sup> , 500 cycles, 91%	823	SCE	6
NiCoAl-LDH/C	1188 850	1 10	6 A g <sup>-1</sup> , 1000 cycles, 100%		SCE	7
NiCoAl-LDH/MWCNT	1035 597	1 10	6 A g <sup>-1</sup> , 1000 cycles, 83.2%	~700	Hg/HgO	8
NiAl-LDH/NF	795 220	0.5 10	2.5 A g <sup>-1</sup> , 1000 cycles, 80%		SCE	9
Al doped Ni(OH) <sub>2</sub> /NF	2122.6 1389.4	1 6	1 A g <sup>-1</sup> , 500 cycles, 78%	1800	SCE	10
NiAl-LDH/NF	701 164	0.5 5	2.5 A g <sup>-1</sup> , 400 cycles, 94%	~460	SCE	11
LDH-NF	817.7 C g <sup>-1</sup> 564.7 C g <sup>-1</sup> 415.4 C g <sup>-1</sup> 645.6 C g <sup>-1</sup>	2 20 40 2	40 A g <sup>-1</sup> , 4000 cycles, 45.9%	150.3 C g <sup>-1</sup>	SCE	this work
LDH-NF/GNS	357.7 C g <sup>-1</sup> 209.8 C g <sup>-1</sup>	20 40	40 A g <sup>-1</sup> , 4000 cycles, 54.1%	165.6 C g <sup>-1</sup>	SCE	this work

**Table S2** Comparison of the maximum energy density and the corresponding power density and voltage range of the reported nickel or cobalt oxide/hydroxide based hybrid supercapacitors

Positive materials//negative materials	Energy density (Wh kg <sup>-1</sup> )	Power density (kW kg <sup>-1</sup> )	Voltage range (V)	Ref
NiO//C	13	0.04	0-1.5	12
Co3O4//AC	24.9	0.225	0-1.5	13
NiCoOx-GNS//AC	7.6	5.6	0-1.4	14
NiCo2O4-rGO//AC	23.3	0.32	0-1.3	15
NiCoOx//AC	12	0.095	0-1.2	16
NiCo2O4//AC	15.42	~0.8	0-1.5	17
Ni-Zn-Co oxide/hydroxide//C	16.6	2.9	0-1.5	18
Ni(OH)2//GNS	30	1	0-1.6	19
Ni(OH)2//ZnFe2O4	14	0.209	0-1.6	20
Ni(OH)2@3D Ni//AC	21.8	0.66	0-1.3	21
NiCo LDH-Zn2SnO4//AC	23.7	0.28	0-1.2	22
NiO-NF//AC	19	0.12	0.8-1.5	23
NiCo2O4@MnO2-NF//AC	~28	0.4	0-1.5	24
Co(OH)2-NF//GO	11.9	2.54	0-1.2	25
Ni(OH)2-NF//AC	10.5	0.687	0-1.6	26
Ni(OH)2/GNS/NF//AC	11.11		0.2-1.6	27
NiCoOx-NF//AC	22.66	2.13	0-1.5	28
NiO-NF//MWCNT	27.8	0.7	0-1.4	29
LDH-NF/GNS//GNS-NF	31.5	0.4	0-1.6	This work
	19.7	3.2		
	12	8		

1. Yan, L.; Li, R.; Li, Z.; Liu, J.; Fang, Y.; Wang, G.; Gu, Z. Three-dimensional activated reduced graphene oxide nanocup/nickel aluminum layered double hydroxides composite with super high electrochemical and capacitance performances. *Electrochim. Acta* **2013**, *95*, 146-154.
2. Wei, J.; Wang, J.; Song, Y.; Li, Z.; Gao, Z.; Mann, T.; Zhang, M. Synthesis of self-assembled layered double hydroxides/carbon composites by in situ solvothermal method and their application in capacitors. *J. Solid State Chem.* **2012**, *196*, 175-181.
3. Gao, Z.; Wang, J.; Li, Z.; Yang, W.; Wang, B.; Hou, M.; He, Y.; Liu, Q.; Mann, T.; Yang, P.; Zhang, M.; Liu, L. Graphene Nanosheet/Ni<sup>2+</sup>/Al<sup>3+</sup> Layered Double-Hydroxide Composite as a Novel Electrode for a Supercapacitor. *Chem. Mater.* **2011**, *23*, 3509-3516.
4. Yang, W. L.; Gao, Z.; Wang, J.; Ma, J.; Zhang, M. L.; Liu, L. H. Solvothermal One-Step Synthesis of Ni-Al Layered Double Hydroxide/Carbon Nanotube/Reduced Graphene Oxide Sheet Ternary Nanocomposite with Ultrahigh Capacitance for Supercapacitors. *ACS Appl. Mater. Interfaces* **2013**, *5*, 5443-5454.
5. Niu Yulian; Li Ruiyi; Li Zaijun; Fang Yinjun; Liu Junkang High-performance supercapacitors materials prepared via in situ growth of NiAl-layered double hydroxide nanoflakes on well-activated graphene nanosheets. *Electrochim. Acta* **2013**, *94*, 360-366.
6. Xu, J.; Gai, S. L.; He, F.; Niu, N.; Gao, P.; Chen, Y. J.; Yang, P. P. A sandwich-type three-dimensional layered double hydroxide nanosheet array/graphene composite: fabrication and high supercapacitor performance. *J. Mater. Chem. A* **2014**, *2*, 1022-1031.
7. Yu, C.; Yang, J.; Zhao, C. T.; Fan, X. M.; Wang, G.; Qiu, J. S. Nanohybrids from NiCoAl-LDH coupled with carbon for pseudocapacitors: understanding the role of nano-structured carbon. *Nanoscale* **2014**, *6*, 3097-3104.
8. Yang, J.; Yu, C.; Fan, X. M.; Ling, Z.; Qiu, J. S.; Gogotsi, Y. Facile fabrication of MWCNT-doped NiCoAl-layered double hydroxide nanosheets with enhanced electrochemical performances. *J. Mater. Chem. A* **2013**, *1*, 1963-1968.

9. Wang, B.; Liu, Q.; Qian, Z. Y.; Zhang, X. F.; Wang, J.; Li, Z. S.; Yan, H. J.; Gao, Z.; Zhao, F. B.; Liu, L. H. Two steps in situ structure fabrication of Ni-Al layered double hydroxide on Ni foam and its electrochemical performance for supercapacitors. *J. Power Sources* **2014**, *246*, 747-753.
10. Huang, J. C.; Lei, T.; Wei, X. P.; Liu, X. W.; Liu, T.; Cao, D. X.; Yin, J. L.; Wang, G. L. Effect of Al-doped beta-Ni(OH)(2) nanosheets on electrochemical behaviors for high performance supercapacitor application. *J. Power Sources* **2013**, *232*, 370-375.
11. Wang, J.; Song, Y.; Li, Z.; Liu, Q.; Zhou, J.; Jing, X.; Zhang, M.; Jiang, Z. In Situ Ni/Al Layered Double Hydroxide and Its Electrochemical Capacitance Performance. *Energy Fuels* **2010**, *24*, 6463-6467.
12. Wang, D. W.; Li, F.; Cheng, H. M. Hierarchical porous nickel oxide and carbon as electrode materials for asymmetric supercapacitor. *J. Power Sources* **2008**, *185*, 1563-1568.
13. Zhang, C. M.; Xie, L. J.; Song, W.; Wang, J. L.; Sun, G. H.; Li, K. X. Electrochemical performance of asymmetric supercapacitor based on Co<sub>3</sub>O<sub>4</sub>/AC materials. *J. Electroanal. Chem.* **2013**, *706*, 1-6.
14. Wang, H. L.; Holt, C. M. B.; Li, Z.; Tan, X. H.; Amirkhiz, B. S.; Xu, Z. W.; Olsen, B. C.; Stephenson, T.; Mitlin, D. Graphene-nickel cobaltite nanocomposite asymmetrical supercapacitor with commercial level mass loading. *Nano Research* **2012**, *5*, 605-617.
15. Wang, X.; Liu, W. S.; Lu, X. H.; Lee, P. S. Dodecyl sulfate-induced fast faradic process in nickel cobalt oxide-reduced graphite oxide composite material and its application for asymmetric supercapacitor device. *J. Mater. Chem.* **2012**, *22*, 23114-23119.
16. Tang, C. H.; Tang, Z.; Gong, H. Hierarchically Porous Ni-Co Oxide for High Reversibility Asymmetric Full-Cell Supercapacitors. *J. Electrochem. Soc.* **2012**, *159*, A651-A656.
17. Lu, X. F.; Wu, D. J.; Li, R. Z.; Li, Q.; Ye, S. H.; Tong, Y. X.; Li, G. R. Hierarchical NiCo<sub>2</sub>O<sub>4</sub> nanosheets@hollow microrod arrays for high-performance asymmetric supercapacitors. *J. Mater. Chem. A* **2014**, *2*, 4706-4713.
18. Wang, H. L.; Gao, Q. M.; Hu, J. Asymmetric capacitor based on superior porous Ni-Zn-Co oxide/hydroxide and carbon electrodes. *J. Power Sources* **2010**, *195*, 3017-3024.

19. Hu, C. C.; Chen, J. C.; Chang, K. H. Cathodic deposition of Ni(OH)(2) and Co(OH)(2) for asymmetric supercapacitors: Importance of the electrochemical reversibility of redox couples. *J. Power Sources* **2013**, *221*, 128-133.
20. Shanmugavani, A.; Selvan, R. K. Synthesis of ZnFe<sub>2</sub>O<sub>4</sub> nanoparticles and their asymmetric configuration with Ni(OH)(2) for a pseudocapacitor. *RSC Adv.* **2014**, *4*, 27022-27029.
21. Su, Y. Z.; Xiao, K.; Li, N.; Liu, Z. Q.; Qiao, S. Z. Amorphous Ni(OH)(2) @ three-dimensional Ni core-shell nanostructures for high capacitance pseudocapacitors and asymmetric supercapacitors. *J. Mater. Chem. A* **2014**, *2*, 13845-13853.
22. Wang, X.; Sumboja, A.; Lin, M. F.; Yan, J.; Lee, P. S. Enhancing electrochemical reaction sites in nickel-cobalt layered double hydroxides on zinc tin oxide nanowires: a hybrid material for an asymmetric supercapacitor device. *Nanoscale* **2012**, *4*, 7266-7272.
23. Inoue, H.; Namba, Y.; Higuchi, E. Preparation and characterization of Ni-based positive electrodes for use in aqueous electrochemical capacitors. *J. Power Sources* **2010**, *195*, 6239-6244.
24. Xu, K. B.; Li, W. Y.; Liu, Q.; Li, B.; Liu, X. J.; An, L.; Chen, Z. G.; Zou, R. J.; Hu, J. Q. Hierarchical mesoporous NiCo<sub>2</sub>O<sub>4</sub>@MnO<sub>2</sub> core-shell nanowire arrays on nickel foam for aqueous asymmetric supercapacitors. *J. Mater. Chem. A* **2014**, *2*, 4795-4802.
25. Salunkhe, R. R.; Bastakoti, B. P.; Hsu, C. T.; Suzuki, N.; Kim, J. H.; Dou, S. X.; Hu, C. C.; Yamauchi, Y. Direct Growth of Cobalt Hydroxide Rods on Nickel Foam and Its Application for Energy Storage. *Chemistry-a European Journal* **2014**, *20*, 3084-3088.
26. Huang, J. C.; Xu, P. P.; Cao, D. X.; Zhou, X. B.; Yang, S. N.; Li, Y. J.; Wang, G. L. Asymmetric supercapacitors based on beta-Ni(OH)(2) nanosheets and activated carbon with high energy density. *J. Power Sources* **2014**, *246*, 371-376.
27. Wang, X.; Liu, J. Y.; Wang, Y. Y.; Zhao, C. M.; Zheng, W. T. Ni(OH)(2) nanoflakes electrodeposited on Ni foam-supported vertically oriented graphene nanosheets for application in asymmetric supercapacitors. *Mater Res Bull* **2014**, *52*, 89-95.



28. Wang, Y. M.; Zhang, X.; Guo, C. Y.; Zhao, Y. Q.; Xu, C. L.; Li, H. L. Controllable synthesis of 3D  $\text{Ni}_x\text{Co}_{1-x}$  oxides with different morphologies for high-capacity supercapacitors. *J. Mater. Chem. A* **2013**, *1*, 13290-13300.
29. Wang, H. W.; Yi, H.; Chen, X.; Wang, X. F. Facile synthesis of a nano-structured nickel oxide electrode with outstanding pseudocapacitive properties. *Electrochim. Acta* **2013**, *105*, 353-361.